SNRC R3-G/C/Pro

Setup: My Base Setup · Franco · Nov 9, 2026

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Type	Indoor carpet
Grip / moisture	Medium

FRONT SUSPENSION

ACKERMANN	
Inner steering link shims	0 mm
Outer steering link location	Back
Anti-roll bar	1.6mm
Arms	Standard
Bump steer: outer steering link shims	0 mm
Camber	-1 degrees
CAMBER LINK	
Inner location	Back outside
Inner shims	2 mm
Outer shims	0 mm
Caster	4 degrees
FF mount	Standard
FF mount inserts	0 mm
FR mount	Standard
FR mount inserts	0 mm
Hubs & steering blocks	Composite 8-deg block
Ride height	5 mm
Shocks: tower mounts	Middle
Steering bell crank	Aluminum
Steering: bell crank arm shims	0 mm
Toe	-1 degrees
Tower	Graphite
Track: wheel hexes	5mm
WHEELBASE	
Arm shims - F/R	1.5 / 0 mm
Hub shims - F/R	1.5 / 1 mm

REAR SUSPENSION

Anti-roll bar	1.4mm
Anti-roll bar arm mounts	Middle
Arms	Standard
Camber	-2 degrees
CAMBER LINK	
Inner location	Front outside
Inner shims	2 mm
Outer location	Inside
Outer shims	2 mm
RF mount	Standard
RF mount inserts	0 mm
Ride height	5,3 mm
RR mount	Standard
RR mount inserts	0 mm
Shocks: tower mounts	Middle
Toe	+2 mm
Tower	Graphite
Track: wheel hexes	5mm
Uprights	Composite
Wheelbase: arm shims - F/R	2 / 0 mm

BODY & CHASSIS

Battery position	Mitt links
Body	Hyrax LMH
Bumper	Flex Bumper
FLEX	
Chassis	2.0mm Graphite
Upper deck - front	Graphite
Upper deck - rear	Graphite

ELECTRONICS

Battery brand	Gens Ace
Battery C rating	130 C
Battery capacity	6600 mAh
Battery model	Gens ace Redline 2.0
ESC brand	Hobbywing
ESC model	G3S 60A
Motor brand	Ruddog
Motor Kv constant	17,5T Kv
Motor model	RCK 17,5T V2
Motor wind	17.5 turns
Radio brand	Flysky
Radio model	Noble NB4
Receiver brand	Flysky
Receiver model	Standard
Steering servo brand	SRT
Steering servo model	Low Profil

NOTES 1-2C

SHOCKS

	FRONT	REAR
Oil weight	500 cst	500 cst
Pistons	2-hole	2-hole
Spring cups	-3mm	-3mm
Springs	2,5-2,8kg Xray	2,6kg Xray
Shock oil brand	Ultimate	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	Spool cst	5,000 cst
Diff fluid mass	0 g	1.3 g
Diff fluid brand	Ultimate	
Front diff type	Spool	
Rear diff gear type	Plastic	

DRIVETRAIN

Drive ratio - internal	1.9
Driveshafts - front	38mm 3.0pin CVD
Driveshafts - rear	46mm 2.0pin S2 CVD
Front drive type	Spool
Pinion	38 teeth
Spur	100 teeth

TIRES

	FRONT	REAR
Tire brand / type	28	–
Wheel brand / type	Matrix	Matrix