

Awesomatix A800MMX/MMCX

Setup: Indoor MST Estenfeld · [Jogi baer](#) · Oct 24, 2026

so dialed
Open/save in RC Setup App →



Scan to open
in the app

TRACK

Track	MST Estenfeld
Type	Indoor astroturf
Grip / moisture	Medium/Low / Dry
Surface / layout	Medium / Medium
Air temp	30°C (86°F)

FRONT SUSPENSION

Anti-roll bar	<u>1.1mm 1 strip</u>
Bellcrank position	Forward
Camber	-1.5 degrees
Caster	4 degrees
Differential height	Low
Downstop	5.6 mm
Lower arms	Standard 1+9.0 (#C04M1+9.0)

LOWER ARMS

Inner pivot spacers - front	1.0 mm
Inner pivot spacers - rear	1.0 mm
Outer stud spacers	0 mm
Ride height	5.0 mm
Steering arms	<u>Kit</u>
Steering blocks	<u>Kit</u>
Steering crank type	Kit

STEERING LINK

Inner stud spacers	1.0 mm
Outer stud location	Front
Outer stud spacers	3.5 mm
Steering rack spacers	0 mm
Toe	+1 degrees
Track: wheel hexes	<u>Standard</u>

UPPER ARMS

Inner stud location - front	1 - Inside
Inner stud location - rear	1 - Inside
Inner stud spacers - front	3.5 mm
Inner stud spacers - rear	3 mm
Outer stud spacers	1.75 mm

REAR SUSPENSION

Anti-roll bar	<u>1.0mm No strip</u>
Camber	-2 degrees
Caster	2 degrees
Differential height	Low
Downstop	4.8 mm
Lower arms	Standard 1+8.0 (#C04M1+8.0)

LOWER ARMS

Inner pivot spacers - front	1.0 mm
Inner pivot spacers - rear	1.0 mm
Outer stud spacers	0 mm
Ride height	5.2 mm
Steering arm	<u>Kit</u>
Steering blocks	<u>Kit</u>
Toe	2 degrees

TOE LINK

Inner stud spacers	0 mm
Outer stud spacers	3.75 mm
Track: wheel hexes	<u>Standard</u>
Upper arm mounts	<u>Kit</u>

UPPER ARMS

Inner stud location - front	A - Inside
Inner stud location - rear	A - Inside
Inner stud spacers - front	2.75 mm
Inner stud spacers - rear	2.75 mm
Outer stud spacers	1.75 mm

TIRES

	FRONT	REAR
Tire additive	CS Highgrip	CS Highgrip
Tire brand / type	Ruddog RR30C	Ruddog RR30C

SHOCKS

	FRONT	REAR
A distance	2.0 mm	3.0 mm
B distance	2,4 mm	2.8 mm
Damper	Kit (#D2.2-S-P)	Kit (#D2.2-S-P)
Oil weight	450 cst	450 cst
PSS	0 %	0 %
Rotor	<u>Kit</u>	<u>Kit</u>
Springs	<u>Soft</u>	<u>Soft</u>
SRS/RHS arrangement	I	I
Shock oil brand	Hudy	

DIFFERENTIALS

	FRONT	REAR
Diff pulley	38T	38T
Diff type	Spool	Gear

DRIVETRAIN

Belt anti-skip system	None
Belts	<u>Kit</u>
Drive ratio - internal	1.9
Driveshafts - front	Standard
Driveshafts - rear	Standard

BODY & CHASSIS

Chassis	1.2mm Stahl WeiRC
Motor mount screw positions	1 - Front, 2, 3, 4, 5
Top stiffener - front	None
Top stiffener - rear	None
Upper deck - front	<u>MMX</u>
Upper deck - rear	<u>MMX</u>
Upper deck screws	C, D, F