



TRACK	
Type	Outdoor asphalt
Grip / moisture	Medium

FRONT SUSPENSION	
Ackermann: outer steering link location	Front
Anti-roll bar	2.4 mm
Axle position	High / mid
Bump steer: outer steering link shims	2 mm
Camber - L/R	-1.5 degrees
Caster: upper arm shims	4 mm
Downstop	0 mm
Lower arms	Kit
Ride height	9 mm
Servo saver length	Med
Servo saver width	8 mm
Shocks: tower mounts	Mid
Steering arm	Kit
Toe	-1 degrees

TRACK	
Lower arm ball gap	2.5 mm
Lower arm mounts	Wide
Wheel offset	0.6 mm
Upper arms	Kit
Upper arms: mount inserts	Up
Uprights	Kit
Wheelbase: lower arm shims	Long

REAR SUSPENSION	
Anti-roll bar	2.6 mm
Camber - L/R	-3
Downstop	8 mm
Lower arms	Kit
Lower arms: mount inserts	Down
Ride height	7 mm
SHOCKS	
Arm mounts	In
Tower mounts	Mid
Toe	3 degrees
Track: wheel offset	0.5 mm
Upper arms	Kit
UPPER ARMS	
Mount inserts	In
Outer shims	2.0 mm
Uprights	Kit

ENGINE	
Engine brand	Os
Fuel	I-tech

TIRES		
	FRONT	REAR
Tire brand / type	69	76

SHOCKS		
	FRONT	REAR
Oil weight	650 cst	650 cst
Pistons	1 x 1.0mm	2 x 1.0mm
Springs	V8.2 Hard	V8.2 Hard
Stroke	10.9 mm	14.7 mm

DRIVETRAIN	
Clutch bell gap	0.55 mm
Clutch shoes	Yellow
Clutch spring pre-load	1.8 mm
Clutch springs	Kit
Driveshafts - front	Kit
Driveshafts - rear	Kit
Pinion - 1st	19 teeth
Pinion - 2nd	25 teeth
Spur - 1st	61 teeth
Spur - 2nd	57 teeth

BODY & CHASSIS	
Battery tray	Kit
Body	Hyper diablo
Body mount height - rear	4
Chassis	Kit
Front flex screws	Yes