# 1RC Super Modified 1/18

Setup: 2026-11-14 On Track RC Hobbies · George Mari · Nov 16, 2026

so dialed
Open/save in RC Setup App →

Scan to open in the app

| EVENT | |
|---|---|
| Event | 2026-11-14 Weekly club race |
| Class | Super Modified |

| TRACK | |
|---|---|
| Track | On Track RC Hobbies |
| Type | Indoor carpet |
| Grip / moisture | High / Dry |
| Surface / layout | Smooth / Tight |

| RESULTS | |
|---|---|
| Race type | Main |
| Race number | A |
| Best lap | 2.16 s |
| Average lap | 2.323 s |
| Laps / time | 100 / 3:53.310 |

## FRONT SUSPENSION

| | |
|---|---|
| Kingpins | **Solid** |
| LF caster | **+2** |
| RF caster | **+2** |
| Servo arm hole | **Lower** |
| Servo arm type | **Servo saver** |

## TIRES

| | |
|---|---|
| LF tire compound | **Soft** |
| LR tire compound | **Soft** |
| RF tire compound | **Standard** |
| RR tire compound | **Standard** |

**NOTES** Glue on outside 1/8 inch of RF tire.

## ESC SETTINGS

| BRAKE | |
|---|---|
| Drag force | **0 %** |
| Initial force | **0 %** |
| Max force | **50 %** |
| Low voltage cut-off | **Disabled** |
| Max reverse force | **50 %** |
| Neutral range | **9 %** |
| Overheat warning | **Enabled** |
| Running mode | **FWD / Brake** |
| Start mode / punch level | **4** |
| Timing | **0 degrees** |

## REAR SUSPENSION

| | |
|---|---|
| LR hex offset | **0 mm** |
| RR hex offset | **0 mm** |

**NOTES** No rear steer.

## BODY & CHASSIS

| | |
|---|---|
| Motor heatsink | **Yes** |
| Top wing mount hole | **Standard wing mount not adjustable** |

## ELECTRONICS

| | |
|---|---|
| Battery brand/model | **Turnigy** |
| Battery capacity | **300 mAh** |
| Battery cells | **2** |
| Battery type | **LiPo** |
| ESC | **1RC** |
| Motor brand/model | **1RC** |
| Motor Kv constant | **10,000 Kv** |
| Radio | **Flysky GT-5** |
| Radio dual-rate | **75 %** |
| Radio EPA brake | **100 %** |
| Radio EPA throttle | **100 %** |
| Receiver | **Flysky GT2E** |
| Servo | **1RC** |
| Transponder ID | **0824** |

**NOTES** Steering Left EPA - 55; Steering Right EPA - 60; Steering EXP - 15 pct; Steering trim - L70

## SHOCKS

| | |
|---|---|
| LF body | **Plastic** |
| LF grease | **AE Green Slime** |
| LF o-ring | **Clear** |
| LF pre-load | **1 mm** |
| LF spring | **Short Medium** |
| LF stroke | **6.7 mm** |
| LR body | **Plastic** |
| LR grease | **AE Green Slime** |
| LR o-ring | **Clear** |
| LR pre-load | **1 mm** |
| LR spring | **Short Medium** |
| LR stroke | **6.7 mm** |
| RF body | **Plastic** |
| RF grease | **AE Green Slime** |
| RF o-ring | **Clear** |
| RF pre-load | **0 mm** |
| RF spring | **Hard** |
| RF stroke | **6.7 mm** |
| RR body | **Plastic** |
| RR grease | **AE Green Slime** |
| RR o-ring | **Clear** |
| RR pre-load | **0 mm** |
| RR spring | **Medium** |
| RR stroke | **6.7 mm** |
| Shock caps | **Drilled** |