TLR 8IGHT-X

Setup: My Base Setup · Kayne Hughes · Oct 29, 2020

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK	
Track	Bop
Type	Outdoor loose/loamy
Grip / moisture	Medium / Dry
Surface / layout	Bumpy / Medium

RESULTS	
Best lap	22.2 s
Average lap	24 s

FRONT SUSPENSION

A mount inserts	0.5 up
Anti-roll bar	2.5mm
Arm inserts	Plastic
Axle height	Low
B mount inserts	0 middle
Camber	-2.5 degrees
CAMBER LINK	
Inner stud location	1 - Inside bottom
Outer stud location	A - Inside
Hub carrier	Aluminum 17.5 deg
Kick-up	12 degrees
Ride height	27 mm
SHOCKS	
Arm mounting hole	B - Outside
Tower mounting hole	3 - Middle-out
STEERING LINK	
Inner stud location	Middle
Inner stud spacers	1 mm
Outer stud spacers	2 mm
Toe	-1 degrees
Tower	Aluminum
Wheel hex	Kit

NOTES 28 mm droop

BODY & CHASSIS

Body	Kit
Center diff brace	Kit
Front brace	Kit
Front chassis brace	Kit
Rear wing	Jc wing

NOTES No center rib

REAR SUSPENSION

Anti-roll bar	2.6
Anti-squat / C block inserts	2.0 degrees - 0
Arm inserts	Plastic
Axle height	Low
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Inside mid-bottom
Outer stud location	D - Outside
Hub	Aluminum
Mud guards	Kit
Ride height	27 mm
Shock location	Front of arm
SHOCKS	
Arm mounting hole	B - Outside
Tower mounting hole	3 - Middle
Toe plate / D block insert	-3.0 degrees - 0
Tower	Aluminum
Wheel hex	Kit
Wheelbase (hub spacers)	Front 0mm / rear 3mm (short)

NOTES 25mm droop

ENGINE

Engine brand	o.s
Engine model	AD2
Fuel	Werks 30%
Glow plug	Os p3
Pipe / header	O.s 2060

ELECTRONICS

Radio brand	Sanwa/Airtronics
Radio model	Sanwa mt44
Receiver battery	2500 lipo
Receiver brand	Sanwa/Airtronics
Steering servo brand	Futaba
Steering servo model	Cb700
Throttle servo brand	Futaba
Throttle servo model	Cb700
Transponder ID	7151071

SHOCKS

	FRONT	REAR
Oil weight	40 wt	35 wt
Pistons	8 x 1.2mm	8 x 1.2mm
Shafts	4mm	4mm
Shock length	106.5 mm	119 mm
Shock type	Bladder	Bladder
Springs	Mugen	Mugen
Shock oil brand	Xtr	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	7,000 cst	3,000 cst
Center diff fluid	7,000 cst	
Center diff type	Standard	
Front diff type	Standard	

DRIVETRAIN

Clutch shoes & springs	2 blue aluminum with gold springs, 2 carbon with green springs
Driveshafts - front	Universal
Driveshafts - rear	CVA
Pinion	14 teeth
Spur	48 teeth

TIRES

	FRONT	REAR
Tire brand / type	Jc triple dees	–
Tire compound	Soft	–
Wheel brand / type	Jc	Losi