AE RC10 B74.1

Setup: Soom Series Southport · Ryan Clarke · May 11, 2022

so dialed
Open/save in RC Setup App →

Scan to open in the app

EVENT	
Event	Soom

TRACK	
Track	Southport
Type	Outdoor astroturf
Grip / moisture	High / Dry
Surface / layout	Smooth / Medium

FRONT SUSPENSION

A mount inserts	1 up
Anti-roll bar	1.9mm
Arms	Hard
Axle height	+2 mm
B mount inserts	1 up
Camber	-1 degrees
CAMBER LINK	
Inner stud location	5 - Inside middle
Outer stud spacers	0 mm
Caster block	10 degrees
Differential height	+1mm (1 dot up)
Ride height	15 mm
SHOCKS	
Arm mounting hole	B - Outside
Tower mounting hole	1 - Inside
Steering block arms	Kit
Steering blocks	Kit
Steering link stud spacers - in/out	3/ 0 mm
Steering link: inner stud location	2 - Back
Toe	0 degrees
Tower	Kit
Track: wheel hexes	5mm
Wheelbase: arm spacers	Long (arm forward)

BODY & CHASSIS

	FRONT	REAR
Wing	No	Proline Lw
Battery position	3	
Body	Proline Axis LW	
Chassis	v2	
Chassis brace - front	Plastic & fiberglass	
Chassis brace - front screws	All	
Chassis brace - rear	Plastic & fiberglass	
Chassis brace - rear screws	2 rear (T) screws removed	
Motor mount	Kit	
Rear wing angle	6 degrees	
Top plate brace	None	
Weight: total	1636 g	

REAR SUSPENSION

Anti-roll bar	1.8mm
Arms	Kit
Axle height (hub insert)	+1mm - 1 up / 2 down
C mount	LRC
C mount inserts	0 center
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Outer stud mount spacers	1 mm
Outer stud spacers	2 mm
D mount	LRC
D mount inserts	1 in
Differential height	+1mm (1 dot up)
Hubs	Kit
Ride height	15 mm
SHOCKS	
Arm mounting hole	B - Middle
Tower mounting hole	2 - Middle
Tower	Kit
Track: wheel hexes	5mm
WHEELBASE	
Arm spacers	Short (arm forward)
Hub spacers	Middle

TIRES

	FRONT	REAR
Tire brand / type	Schumacher Dart	Schumacher dart
Tire compound	Yellow	Yellow
Tire insert	Schuey Blue	Rude Bits Cheater
Tire prep	2 in 2 out off Glued Sidewalls	1 off out
Wheel brand / type	JConcepts	JConcept

SHOCKS

	FRONT	REAR
Bodies	12 x 23mm Fox Kshima	12 x 27mm Fox Kashima
Cup offset	9 mm	0 mm
Eyelet length	Long	Long
Limiters - int/ext	0 / 1 mm	0 / 1 mm
Oil weight	45 wt	35 wt
Pistons	2 x 1.6mm Thin	2 x 1.7 Thin
Shafts	3 x 23mm Chrome	3x27.5mm v2 Chrome
Springs	v2 Yellow	v2 Blue
Stroke	22.5 mm	27.5 mm
Shock oil brand	Team Associated	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	10,000 cst	7,000 cst
Diff gears	Plastic	Plastic
Diff mass	36 g	36 g
Center diff fluid	500,000 cst	
Center diff gears	Plastic	
Center diff mass	37 g	
Diff fluid brand	AE	

DRIVETRAIN

Clutch pads	Na
Clutch tightness	0 mm
Drive ratio - internal	2.5
Drive type	Differential
Driveshafts - front	DCV
Driveshafts - rear	66m CVA
Pinion	21 teeth
Spur	78 teeth

NOTES Centre Diff all day

ELECTRONICS

Battery brand	Intellect Pioneering
Battery capacity	4200 mAh
ESC brand	Hobbywing
ESC model	Xr10 pro
ESC settings	36 degrees turbo 24k drive freq Throttle rate 6 4k brake freq 16 brake rate
Motor brand	Hobbywing
Motor model	V10 g3
Motor wind	6.5 turns
Radio brand	Sanwa/Airtronics
Radio model	Exzes ZZ
Servo brand	Highest
Servo model	D1000