Kyosho Inferno MP10e

Setup: My Base Setup · Di SandroGiovanni CarfizziStefania · Aug 16, 2022

so dialed
Open/save in RC Setup App →

Scan to open in the app

FRONT SUSPENSION

Anti-roll bar	2.4 mm
Anti-roll bar ball position	0 mm
Arms	Soft
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Inside middle
Outer stud location	A - Inside
FF (A) mount inserts (kick-up)	Center
FR (B) mount inserts (kick-up)	Up
Hub carrier	Hard 17.5 degree
Hub carrier inserts (caster)	0 degrees
Ride height	26 mm
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	1 - Inside
Steering block	TKI4
Steering link: inner stud location	3 - Mid-front
Steering: center link orientation	Holes rearward
Tower	Kit
Wheel hex	Standard

REAR SUSPENSION

Anti-roll bar	2.7 mm
Anti-roll bar ball position	0 mm
Arm inserts (track)	Long
Arms	Soft
Camber	-2 degrees
CAMBER LINK	
Inner stud location	1 - Inside bottom
Outer stud location	D - Outside up
Hub	Hard
Hub inserts (track/axle height)	Up and in
RF (C) mount inserts (anti-squat)	+2 degrees
Ride height	28 mm
RR (D) mount inserts (toe)	High roll center / 3 deg toe
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	1 - Inside
Tower	Kit
Wheel hex	Standard
Wheelbase (hub spacers)	Front 3mm / rear 2mm

BODY & CHASSIS

Body	MP10e 0.8mm
Chassis	Kit
Rear wing	Kyosho Plastic with Wickerbills
Rear wing angle	High
Rear wing mount	Kit

SHOCKS

	FRONT	REAR
Bodies	Short	Long
Oil weight	550 cst	450 cst
Pistons	5 x 1.5mm	5 x 1.5mm
Shock length	102 mm	118 mm
Springs	70mm Red	81mm Light purple
Shock oil brand	Kyosho	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	4,000 cst	3,000 cst
Diff type	Standard	Standard
Center diff fluid	6,000 cst	
Center diff type	Standard	

DRIVETRAIN

Drive ratio - internal	3.31
Driveshaft - center front	Kit (IFW430)
Driveshaft - center rear	Kit
Driveshafts - front	94mm Universal
Driveshafts - rear	94mm Universal
Pinion	14 teeth
Spur	46 teeth

ELECTRONICS

Battery brand	Gens Ace
Battery capacity	5000 mAh
Battery model	4s