AE RC10 B6.2

Setup: A1 raceway · Ryan Clarke · Aug 14, 2021

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK	
Track	A1 Raceway
Type	Outdoor astroturf
Grip / moisture	Medium / Dry
Surface / layout	Bumpy / Open

FRONT SUSPENSION

Anti-roll bar	None
Arms	Gull-wing
Axle height	2 mm
Bulkhead	Brass
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	2 mm
Outer stud location	A - Inside
Caster	30 deg - Kick-up: 25 / Block insert: +5
Ride height	18 mm
SHOCKS	
Arm mounting hole	C - Outside
Tower mounting hole	3 - Outside
STEERING LINK	
Inner stud spacers	2 mm
Outer stud spacers	0 mm
Steering plate / arm	+1mm
Steering stop spacers	0 mm
Toe	0 degrees
Tower	Gull-wing
Track: wheel hexes	5mm Aluminum
Trail	4 mm
Wheelbase: hub carrier spacers	Long (forward)

TIRES

	FRONT	REAR
Tire brand / type	Schumacher Lp Cut Stagger	Schumacher Mini Dart
Tire compound	Yellow	Yellow
Tire insert	None	Open-cell
Wheel brand / type	JConcepts	JConcepts

REAR SUSPENSION

Anti-roll bar	None
Arms	73 mm
Axle height (hub insert)	0 (0/3 up)
C mount	Aluminum
C mount inserts	0.5 in
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	2 mm
Outer stud mount spacers	2 mm
Outer stud spacers	2 mm
D mount	Aluminum
D mount inserts	0.5 down
Differential height	0 mm
Hubs	Plastic
Ride height	18 mm
Shock location	Front of arm
SHOCKS	
Arm mounting hole	B - Middle
Tower mounting hole	1 - Inside
Track: wheel hexes	7mm
WHEELBASE	
Arm spacers	Short (forward)
Hub spacers	Short (forward)

BODY & CHASSIS

	FRONT	REAR
Wing	Kit	Kit
Battery position	Front hole / 3	
Body	Kit	
Chassis	Kit	
Rear wing angle	6 degrees	
WEIGHT		
Electronics plate	Steel 36g	
Servo	Steel 24g	

SHOCKS

	FRONT	REAR
Bodies	Team FOX	Team FOX
Cup offset	5 mm	0 mm
Eyelet length	Short	Long
Limiters (external)	0 mm	1 mm
Limiters (internal)	0	0
Oil weight	500 cst	350 cst
Pistons	2 x 1.6 thin	2 x 1.7 thin
Shafts	x2 3x21mm Chrome	x2 3x27.5mm Chrome
Springs	v2 Red	v2 White
Stroke	22.5 mm	27.5 mm
Shock oil brand	CORE	

DRIVETRAIN

Clutch pads	Kit
Clutch type	Slipper
Differential fluid	Ball diff cst
Differential type	Ball
Driveshaft CVA pin location	Towards wheel
Driveshafts	67mm
Pinion	23 teeth
Spur	78 teeth
Transmission gears	3
Transmission orientation	Laydown