Tekno SCT410.3

Setup: Pro4 · James CupCake Carrigan (Tekno Rc) · Jan 25, 2021

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK	
Type	Indoor clay
Grip / moisture	High / Dry
Surface / layout	Bumpy / Medium

RESULTS	
Best lap	15 s

FRONT SUSPENSION

A mount	Aluminum
A mount inserts	1 down
Anti-roll bar	2.6 mm
B mount	Aluminum
B mount inserts	0.5 out
Camber	-2 degrees
CAMBER LINK	
Inner stud location	4 - Outside top
Outer stud location	A - Inside
Droop	109 mm
Kick-up angle	11 degrees
Ride height	18 mm
Servo saver tightness	Locked
SHOCKS	
Arm mounting hole	A - Inside
Tower mounting hole	3 - Middle-in
STEERING LINK	
Inner stud location	Middle
Inner stud spacers	Over 0 / under 4
Outer stud spacers	Over 2 / under 2
Sweep	0 degrees
Toe	+2 degrees
Tower	Kit
Wheel hex	Aluminum mm

REAR SUSPENSION

Anti-roll bar	2.5 mm
C mount	Aluminum
C mount inserts	0.5 in
Camber	-2 degrees
CAMBER LINK	
Inner stud location	7th hole
Outer stud location	A - Inside
D mount	Aluminum
D mount inserts	1 down and out
Droop	120 mm
Ride height	18 mm
SHOCKS	
Arm mounting hole	B - Outside
Tower mounting hole	3 - Middle-in
Toe	-2 degrees
Tower	Kit
Wheel hex	Lightened steel
Wheelbase (hub spacers)	Front 1mm / rear 4mm

BODY & CHASSIS

Body mount - front	10mm offset / 15 degree
Body mount - front height	2
Body mount - rear	0mm offset / 15 degrees
Body mount - rear height	4
Brace - front	Kit
Brace - rear	None
Center diff brace	Kit
Center diff mount	Composite

SHOCKS

	FRONT	REAR
Caps	Aluminum vented	Aluminum non-vented
Oil weight	350 cst	200 cst
Pistons	5 x1.2 - 2 x1.0	5x1.2 - 2x1.0
Rebound	0 %	0 %
Shafts	Steel	Steel
Shock type	Emulsion	Emulsion
Springs	Yellow LF	Pink LF
Shock oil brand	Tekno	

DIFFERENTIALS

	FRONT	REAR
Diff fluid	7,000 cst	5,000 cst
Center diff fluid	10,000 cst	

DRIVETRAIN

Pinion	16 teeth
Spur	44 teeth