Xpress EXECUTE FT1

Setup: Nationals West London (2022) · Megan Davidson (Speed RC) · Dec 22, 2022

so dialed
Open/save in RC Setup App →

Scan to open in the app

TRACK

Track	Stafford
Type	Outdoor asphalt
Grip / moisture	Medium/Low
Surface / layout	Smooth/Medium / Medium/Tight

FRONT SUSPENSION

ACKERMANN	
Inner steering link shims	1 mm
Outer steering link location	1 - Outside
Anti-roll bar	1.3 mm
Arms	Hard
Bumpsteer: outer steering link shims	1.0 mm
Camber	-2.5 degrees
CAMBER LINK	
Inner mount	Inside
Inner mount shims	1 mm
Inner stud shims	1 mm
Outer stud shims	1 mm
Differential height	Low
Downstop	6.0 mm
FF mount	Aluminum
FF mount inserts	0 center
FR mount inserts	0.5 up
FR mounts	Split aluminum
Ride height	5.5 mm
Servo saver stud shims	4.0 mm
SHOCKS	
Arm mount shims	0 mm
Tower mount shims	0 mm
Tower mounting hole	3 - Outside
Toe	+1 degrees
Tower	Graphite
Track: wheel hexes	5mm Red
Wheelbase: arm shims - F/R	1 / 1 mm

NOTES Adjustable Ackerman steering block (8.5)
22 deg steering throw

REAR SUSPENSION

Anti-roll bar	1.2 mm
Arms	Hard
Camber	-2 degrees
CAMBER LINK	
Inner mount	Inside
Inner mount shims	0 mm
Inner stud shims	0 mm
Outer stud location	Inside
Outer stud shims	1 mm
Downstop	4.6 mm
OPCS link stud spacers - inner/outer	- / - mm
RF mount	Aluminum
RF mount inserts	1 down and in
Ride height	5.6 mm
RR mount inserts	1 up
RR mounts	Aluminum
SHOCKS	
Arm mount shims	1 mm
Tower mount shims	0 mm
Tower mounting hole	3
Tower	Xpress Graphite 3.0mm Rear Short Shock
Track: wheel hexes	5mm Red
Wheelbase: arm shims - F/R	0/2 mm

TIRES

	FRONT	REAR
Tire additive	Spider Blue	Spider Blue
Tire additive area	Inside, Mid-in, Mid-out, Outside	Inside, Mid-in, Mid-out, Outside
Tire brand / type	Ride FWD Belted Cut Slick (BRCA)	Ride FWD Belted Cut Slick (BRCA)
Tire compound	Rubber	Rubber
Tire insert	ETS Spec	ETS Spec
Wheel brand / type	Ride	Ride

NOTES Front tyres on backwards??

SHOCKS

	FRONT	REAR
Cap	Ventilated	Ventilated
Oil weight	450 cst	350 cst
Pistons	4-hole	4-hole
Rebound	0 %	0 %
Springs	XRay 4S Spring-Set Progressive C = 2.5-2.8	Silver medium
Stroke	10.5 mm	10.5 mm
Shock oil brand	Team Associated	

DIFFERENTIALS

Diff fluid brand	Arrowmax
Front diff fluid	1,000,000 cst
Front diff fluid mass	1.2 g

NOTES +2 up rear

DRIVETRAIN

Drive ratio - final	2.94
Drive ratio - internal	1.9
Driveshafts - front	39.3mm Univ Double Joint
Front drive type	Differential
Pinion	44 teeth
Spur	68 teeth

BODY & CHASSIS

Battery position	Parallel Shorty
Body	Blitz MK9
BODY MOUNTS	
Front hole	2
Rear hole	2
Body position	Neutral
FLEX	
Chassis	Graphite 2.25mm
Stiffener post	None
Upper deck	Graphite 2mm
Upper deck screws	Front, Front-mid, Rear
Rear wing	Stock cut to smallest cut lines
Screws & turnbuckles	Titanium
Weight balance (F/R)	65 / 35

ELECTRONICS

Battery brand	**Intellect Pioneering**
Battery C rating	**90**
Battery capacity	**6200 mAh**
ESC brand	**Hobbywing**
ESC model	**XeRun XR10 Justock 60Amp G3**
ESC settings	**Punch: 7 Max Brake Force: 100% Drag Brake: 0**
Motor brand	**Hobbywing**
Motor model	**Justock G2.1 (HW38020321)**
Motor wind	**17.5 turns**
Radio brand	**Futaba**
Radio EPA steering	**107/107 %**
Radio EPA throttle	**100 %**
Radio model	**T4PM**
Receiver brand	**Futaba**
Receiver model	**R304SB**
Steering servo brand	**Ludicrous**
Steering servo model	**Low Profile**
Transponder ID	**7382723**

NOTES Sub Trim Str: R1
Str Expo: -90
Speed Turn: 65
DR: 80
Trim: 0