AE RC10 SC6.1

Setup: Burlington setup · Kyle Swanson · Jun 24, 2022

so dialed
Open/save in RC Setup App →

Scan to open in the app

FRONT SUSPENSION

Anti-roll bar	None
Arms	Kit
Axle height	1 mm
Bulkhead	Aluminum Factory Team
Camber	-2 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	1 mm
Outer stud location	B - Outside
Caster	20 deg - Kick-up: 25 / Block insert: -5
Ride height	25 mm
SHOCKS	
Arm mounting hole	B - Middle
Tower mounting hole	2 - Middle
STEERING LINK	
Inner stud spacers	2 mm
Outer stud spacers	1 mm
Steering plate / arm	Kit
Steering stop spacers	0 mm
Toe	+1 degrees
Tower	Kit
Trail	4 mm
Wheel hex	8.5 mm
Wheelbase (hub carrier spacers)	Long (forward)

REAR SUSPENSION

Anti-roll bar	None
Arms	Kit
Axle height (hub insert)	0 (0/3 up)
C mount	Aluminum
C mount inserts	0 - center
Camber	-1 degrees
CAMBER LINK	
Inner stud location	2 - Middle
Inner stud spacers	1 mm
Outer stud location / hub insert	3 holes up / C - Middle up
Outer stud spacers	0
D mount	Aluminum
D mount inserts	0 - center
Differential height	2 mm
Hub	Aluminum FT
Ride height	25 mm
Shock location	Front of arm
SHOCKS	
Arm mounting hole	B - Middle-in
Tower mounting hole	2 - Middle
Wheel hex	7mm
Wheelbase (hub spacers)	Middle

BODY & CHASSIS

Battery position	Front hole / 2
WEIGHT	
Chassis	0g
Electronics plate	13 g esc plate g
Servo	0 g

SHOCKS

	FRONT	REAR
Bodies	v2 12x27.5mm	v2 12x36mm
Cup offset	5 mm	0 mm
Eyelet length	Long	Short
Limiters (internal)	2	1
Oil weight	32.5 wt	30 wt
Pistons	2 x 1.6mm FT v2	2 x 1.7mm FT v2
Shafts	3x27.5mm v2 Ti-N	3x35mm v2 Ti-N
Springs	54mm White	72mm Green - lightest
Stroke	26.5 mm	35 mm
Shock oil brand	Team Associated	

DRIVETRAIN

Clutch pads	Kit
Clutch type	Direct drive
Differential type	Ball
Driveshafts	91mm
Pinion	25 teeth
Spur	81 teeth
Transmission gears	3
Transmission orientation	Layback

TIRES

	FRONT	REAR
Tire brand / type	Rawspeed	–